

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

| IDENTITY AND DISTRIBUTOR'S INFORMATION | | | | | | |
|---|--|---|---|---|-----------------|---------------------------|
| NFPA Rating: Health-2; Flammability-3; Reactivity-0; Special - Manufactured For: UNISOURCE WORLDWIDE, INC. Address: 6600 Governors Lake Parkway Address: Norcross, GA 30071 Phone: 800-UNISOURCE Emergency Response Number: 1-888-660-6737 | | | HMIS Rating: Health-2; Flammability-3; Reactivity-0; Personal Protection-B DOT Hazard Classification: ORM-D Identity (trade name as used on label): <div style="background-color: yellow; padding: 2px;">ALLSTAR D-FEN (U17545)</div> MSDS Number: A00223 Revision: 10 Date Prepared: 10/05/01 Prepared By: DL/IB Information Calls: (770)422-2071 | | | |
| NOTICE: JUDGMENT BASED ON INDIRECT TEST DATA | | | | | | |
| SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION | | | | | | |
| COMPONENTS-CHEMICAL NAMES AND COMMON NAMES <small>(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)</small> | | CAS Number | SARA III LIST | OSHA PEL (ppm) | ACGIH TLV (ppm) | Carcinogen Ref. Source ** |
| ETHANOL | | 64-17-5 | No | 1000 | 1000 | d |
| SODIUM NITRITE | | 7632-00-0 | No | N/E | N/E | d |
| AMMONIUM HYDROXIDE | | 1336-21-6 | No | 35 | 25 | d |
| ISOBUTANE / PROPANE BLEND | | 75-28-5 | No | 800 | 800 | d |
| | | 74-98-6 | No | 1000 | 1000 | d |
| METHANOL | | 67-56-1 | Yes | 200 | 200 | d |
| O-PHENYLPHENOL | | 90-43-7 | Yes | NE | NE | e |
| WARNING: This product contains a chemical or chemicals known to the State of California to cause cancer. | | | | | | |
| SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS | | | | | | |
| Boiling Point: N/A | | | Specific Gravity (H₂O=1): Concentrate Only = 0.880 | | | |
| Vapor Pressure: PSIG @ 70°F (Aerosols): Max.60 | | | Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A | | | |
| Vapor Density (Air = 1): N/E | | | Evaporation Rate (= 1): N/E | | | |
| Solubility in Water: Soluble | | | Water Reactive: No | | | |
| Appearance and Odor: Clear, colorless spray, light airy fragrance. | | | | | | |
| SECTION 3 - FIRE AND EXPLOSION HAZARD DATA | | | | | | |
| FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) NON-FLAMMABLE | | Auto Ignition Temperature: N/E | | Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E | | |
| FLASH POINT AND METHOD USED (non-aerosols): N/A | | EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water. | | | | |
| SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus. | | | | | | |
| Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture. | | | | | | |
| SECTION 4 - REACTIVITY HAZARD DATA | | | | | | |
| STABILITY [X] STABLE [] UNSTABLE | | | HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR | | | |
| Incompatibility (Mat. to avoid): Oxidants, reducing agents, ammonium salts. | | | Conditions to Avoid: Open flame, welding arcs, heat, sparks. | | | |
| Hazardous Decomposition Products: CO, CO ₂ . | | | | | | |
| SECTION 5 - HEALTH HAZARD DATA | | | | | | |
| PRIMARY ROUTES OF ENTRY: [X] INHALATION [] INGESTION [] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS | | | | | | |
| ACUTE EFFECTS | | | | | | |
| Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness. | | | | | | |
| Eye Contact: Mild irritation. | | | Skin Contact: Possible mild irritation. | | | |
| Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea. | | | | | | |
| CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) Overexposure may cause kidney damage, liver abnormalities, brain damage. | | | | | | |
| Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions. | | | | | | |
| EMERGENCY FIRST AID PROCEDURES | | | | | | |
| Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention. | | | | | | |
| Skin Contact: Wash with soap and water. If irritated, seek medical attention. | | | | | | |
| Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention. | | | | | | |
| Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention. | | | | | | |
| SECTION 6 - CONTROL AND PROTECTIVE MEASURES | | | | | | |
| Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH in positive pressure mode. | | | | | | |
| Protective Gloves: Latex, if skin easily irritated. | | | Eye Protection: Safety glasses recommended. | | | |
| Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV. | | | | | | |
| Other Protective Clothing & Equipment: None | | | | | | |
| Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing. | | | | | | |
| SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE | | | | | | |
| Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. | | | | | | |
| Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard. | | | | | | |
| Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F. | | | | | | |
| Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Remove ignition sources. Do not use on polished wood furniture or rayon fabrics. | | | | | | |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only
 THIS MSDS IS CURRENT AS OF September 12, 2001. The DATE PREPARED section is the original date assembled and remains current until a change is necessary. This is tracked internally at the manufacturer by these date codes and therefore must remain as the originating date.

SAP# 1020459

