

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Wear protective eyewear (goggles or face shield), gloves, and protective clothing when using this product. Dry treated areas and articles such as clothing before use. Remove children and pets from treated area until completely dry. Clean surfaces prior to application.

Approved Commercial and Industrial Uses: This product can be applied to organic or inorganic substrates by brushing, dipping, padding, soaking, spraying, or by using foam finishing techniques. Use areas include air filters/materials, bed sheets, blankets, bedspreads, carpets and draperies, mattress pads and ticking, shower curtains, outerwear apparel (jackets, sweaters, sweatshirts, coats, raincoats, overcoats, jerseys, ponchos), athletic and casual shoes. SEE ATTACHED PAGES FOR ADDITIONAL APPROVED COMMERCIAL AND INDUSTRIAL USES.

Approved Residential Uses: Washable walls, floors, carpeting, tubs, vanity tops, window sills, appliances, plastic, vinyl, mattress pads and mattress ticking, underwear, toweling, hosiery. SEE ATTACHED PAGES FOR ADDITIONAL APPROVED RESIDENTIAL USES AND APPLICATION METHODS.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage and disposal. **Pesticide Storage:** Store in original, tightly closed containers below 30°C (86°F) and above 0°C (32°F) in a secure area inaccessible to children and away from food or feed. **Pesticide Disposal:** Residential use - Wastes resulting from the use of this product may be disposed of on site. Commercial/Industrial Use - Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility. **Container Disposal:** Residential use - Securely wrap original container in several layers of newspaper and discard in trash. Commercial use - Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by other procedures approved by state and local authorities.

ENVIROSYSTEMS®

BioShield® 75

MICROBIOSTATIC AGENT*

Active Ingredients:

Octadecylaminodimethyltriethoxysilyl propyl ammonium chloride:	0.75%
Other Ingredients:.....	99.25%
TOTAL	100.00%

*A microbiostatic agent is an agent that inhibits the growth of odor causing bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration, and algae. This product does not protect users or others against food-borne or disease causing bacteria or fungi.

Do not use in any application involving direct or indirect food or drinking water contact.

KEEP OUT OF REACH OF CHILDREN CAUTION

See side panels for additional precautionary statements.

EPA Reg.No. 53053-7
EPA Est. No. 53053-NC-01

Manufactured by: **INDUSCO, LTD.**
2319 Joe Brown Drive
Greensboro, NC 27405
(336) 375-7555 FAX (336) 375-0826

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Causes moderate eye irritation. Avoid contact with skin, eyes and clothing. Harmful if inhaled or absorbed through the skin. Avoid breathing vapors or spray mist. Wear protective eyewear and protective clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum or using the toilet. Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS

Commercial and Industrial uses: This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

De-activation required during clean up if a spill occurs. De-activation of this product can be achieved by the addition of anionic surfactant (such as soap, sulfonates, sulfates) in quantity equivalent to that of this product.

Residential use: This pesticide is toxic to fish. Do not contaminate water by cleaning of equipment or disposal of pesticide. Do not apply directly to water.

FIRST AID

Have the product container or label with you when calling the poison control center or doctor, or going for treatment.

IF ON SKIN: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call poison control center or doctor for treatment advice.

IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.

ESL082008 REV091808

EnviroSystems® BioShield® 75 creates an invisible barrier to inhibit the growth of odor causing bacteria, bacteria and fungi (mold and mildew) which cause staining and discoloration, and algae.

DIRECTIONS FOR USE

Approved commercial and industrial applications

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Wear protective eyewear (goggles or face shield) and gloves when using this product. Dry treated areas and articles such as clothing before use. Remove children and pets from treated area until completely dry.

EnviroSystems® BioShield® 75 can be applied to organic or inorganic substrates by brushing, dipping, padding, soaking, spraying or by using foam finishing techniques.

The substrate can be dried at temperatures from ambient to a maximum of 160° C (320° F) to effect complete condensation of silanol groups and to remove water, solvents and/or traces of methanol from hydrolysis. Optimum application and drying conditions, such as time and temperature, should be determined for each application before use. If necessary, reapply EnviroSystems® BioShield® 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.

Approved commercial and industrial applications

The active ingredient in EnviroSystems® BioShield® 75 is effective against odor causing bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration, and algae as a static agent. EnviroSystems® BioShield® 75 can be used as a final bacteriostatic finish on the following items to impart bacteriostatic/fungistatic (mold and mildew) and algaestatic activity.

- Air filters for furnaces, air-conditioners, air purification devices, automobiles, recirculating air handling systems
- Air filters/materials
- Aquarium filter material
- Bed sheets, blankets, and bedspreads
- Buffer pads (abrasive and polishing)
- Carpets and draperies
- Fiberfill for upholstery, sleeping bags, apparel, where the fiber is cotton, natural down, nylon, polyester, rayon, or wool
- Fiberglass ductboard
- Fire hose fabric
- Humidifier belts
- Mattress pads and ticking
- Men's underwear and outerwear
- Non-woven polyester
- Outerwear apparel (jackets, sweaters, sweatshirts, coats, raincoats, overcoats, jerseys, ponchos)
- Polyurethane and cellulose foam for household, industrial, and institutional mops
- Polyurethane and polyethylene foam, when covered

- Polyurethane foam for packaging and cushioning in non-food contact applications
- Polyurethane foam used as a growth medium for non-food crops and plants
- Roofing materials - defined as shingles, roofing granules, wood shakes, felt, stone and synthetic overcoats
- Sand bags, tents, tarpaulins, sails, and ropes
- Athletic and casual shoes
- Shoe insoles
- Shower curtains
- Socks comprised of nylon, nylon/orlon, cotton/nylon, linen/Lycra, acrylic/polypropylene/nylon/Lycra, wool/silk/nylon/Lycra and wool/acrylic/nylon/Lycra
- Throw rugs
- Toweling made of 100 percent cotton, 100 percent polyester, and blends of the two fibers
- Toilet tank and seat covers
- Umbrellas
- Upholstery made of acetates, acrylics, cotton, fiberglass, nylon, polyester, polyethylene, polyolefins, polypropylene, rayon, spandex, vinyl, wool
- Vacuum cleaner bags and filters
- Vinyl paper-wallpaper for non-food contact surfaces
- Disposable wiping cloths that can be used for multiple purposes such as dusting or washing furniture, cars, walls, windows, floors, appliances, counter tops; the wiping cloths do not impart pesticide properties
- Women's hosiery
- Women's intimate apparel

DIRECTIONS FOR USE

Approved commercial applications in homes, offices, automobiles and the following institutions: schools, hospitals, daycare centers, churches, correctional facilities

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Wear protective eyewear (goggles or face shield) and gloves when using this product. Dry treated areas and articles such as clothing before use. Remove children and pets from treated area until completely dry. Clean surfaces prior to application.

The active ingredient in EnviroSystems® BioShield® 75 is effective against odor causing bacteria and fungi (mold and mildew), bacteria and fungi (mold and mildew) which cause staining and discoloration, and algae as a static agent. EnviroSystems® BioShield® 75 can be used as a final bacteriostatic finish on the following items to impart bacteriostatic/fungistatic (mold and mildew) and algaestatic activity.

- Air filters for furnaces, air-conditioners, air purification devices, automobiles, recirculating air handling systems
- Air filters/materials
- Aquarium filter material
- Bed sheets, blankets, and bedspreads
- Buffer pads (abrasive and polishing)
- Carpets and draperies
- Fiberfill for upholstery, sleeping bags, apparel, where the fiber is cotton, natural down, nylon, polyester, rayon, or wool
- Fiberglass ductboard
- Fire hose fabric
- Humidifier belts
- Mattress pads and ticking

- Men's underwear and outerwear
- Non-woven polyester
- Outerwear apparel (jackets, sweaters, sweatshirts, coats, raincoats, overcoats, jerseys, ponchos)
- Polyurethane and cellulose foam for household, industrial, and institutional mops
- Polyurethane and polyethylene foam, when covered
- Polyurethane foam for packaging and cushioning in non-food contact applications
- Polyurethane foam used as a growth medium for non-food crops and plants
- Roofing materials - defined as shingles, roofing granules, wood shakes, felt, stone and synthetic overcoats
- Sand bags, tents, tarpaulins, sails, and ropes
- Athletic and casual shoes
- Shoe insoles
- Shower curtains
- Socks comprised of nylon, nylon/orlon, cotton/nylon, linen/Lycra, acrylic/polypropylene/nylon/Lycra, wool/silk/nylon/Lycra and wool/acrylic/nylon/Lycra
- Throw rugs
- Toweling made of 100 percent cotton, 100 percent polyester, and blends of the two fibers
- Toilet tank and seat covers
- Umbrellas
- Upholstery made of acetates, acrylics, cotton, fiberglass, nylon, polyester, polyethylene, polyolefins, polypropylene, rayon, spandex, vinyl, wool
- Vacuum cleaner bags and filters
- Vinyl paper-wallpaper for non-food contact surfaces
- Disposable wiping cloths that can be used for multiple purposes such as dusting or washing furniture, cars, walls, windows, floors, appliances, counter tops; the wiping cloths do not impart pesticide properties
- Women's hosiery
- Women's intimate apparel

For Pump Spray Application: Using pump sprayer, spray entire area 4"- 6" from the surface making sure the surface is completely covered. Apply and then let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test for staining and color-fastness of fabrics and carpets by treating and drying a small, concealed area prior to application. One gallon of EnviroSystems® BioShield® 75 treats approximately 200 square feet. When treating coarser substrates, more EnviroSystems® BioShield® 75 may be required due to absorption. A fan may be used to assist in drying carpeting.

For Commercial Spray Application: For commercial application equipment (i.e., carpet/upholstery steamers, rotary jet extraction cleaners, pressure sprayers) apply and then let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test for staining and color-fastness of fabrics and carpets by treating and drying a small, concealed area prior to application. One gallon of EnviroSystems® BioShield® 75 treats approximately 200 square feet. When treating coarser substrates, more EnviroSystems® BioShield® 75 may be required due to absorption. Dry carpet areas and surfaces before re-entry and dry articles before use. A fan may be used to assist in drying carpeting.

For Dipping/Soaking Application: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems® BioShield® 75 to completely submerge item. Completely submerge item in solution for 3 minutes. Remove item and dry. Test for staining and color-fastness of fabrics by treating and drying a small, concealed area prior to application. Do not reuse solution after dipping/soaking.

The substrate can be dried at room temperatures or at temperatures to a maximum of 160° C (320° F), for example in a clothes dryer. Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems® BioShield® 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.

DIRECTIONS FOR USE
For residential applications

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Wear protective eyewear (goggles or face shield) and gloves and protective clothing when using this product. Dry treated areas and articles such as clothing before use. Remove children and pets from treated area until completely dry. Clean surfaces prior to application.

Approved residential uses

The active ingredient in EnviroSystems® BioShield® 75 is effective against odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew) and algae as a static agent.

	Pest controlled	Method of Application
<p>Bedsheets, blankets, bedspreads, curtains, draperies (washable only), underwear, socks, intimate apparel, hosiery, throw rugs, toweling, toilet tank covers, shower curtains, shoe insoles, outerwear apparel (jackets, sweaters, sweatshirts, coats, raincoats, overcoats, jerseys, ponchos). EnviroSystems® BioShield® 75 can be applied to fabrics made of acetates, acrylics, cotton, fiberglass, linen, Lycra, nylon, orlon, polyester, polyethylene, polyolefins, polypropylene, rayon, silk, spandex, vinyl, and wool</p>	<p>Odor causing bacteria, bacteria which cause staining and discoloration, and fungi (mold and mildew)</p>	<p>DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems® BioShield® 75 to completely submerge item. Keep item in solution for 3 minutes. Remove item and wring excess liquid. Drying may be attained by dripping dry or wringing excess liquid from treated item. For larger items (e.g., bedspreads, curtains, draperies), place in washing machine on spin cycle to aid in the removal of excess liquid. Test staining and color-fastness of fabric and carpets by treating and drying a small concealed area prior to application. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160 °C (320 °F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems® BioShield® 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, and mildew stains return.</p> <p>SPRAY: Clean surface prior to application. Using a trigger pump sprayer or pressure sprayer, spray the entire surface area 4"-6" from the surface making sure the surface is completely covered. Let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test staining and color-fastness of fabric by treating and drying a small concealed area prior to application. If necessary, reapply EnviroSystems® BioShield® 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, and mildew stains return.</p>
<p>Air filters and air filter material for</p> <ul style="list-style-type: none"> • Furnaces, air conditioners • Air purification systems • Automobiles • Recirculating air handling systems • Vacuum cleaner filters • Aquariums 	<p>Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew), and algae</p>	<p>SPRAY: When treating filters, remove filter from the unit. Using a trigger pump sprayer or pressure sprayer, spray the entire surface area 4"- 6" from the surface making sure the surface is completely covered. Apply and then let stand until dry. If necessary, reapply EnviroSystems® BioShield® 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.</p>

	Pest controlled	Method of Application
Carpeting	Odor causing bacteria, bacteria which cause staining and discoloration, and fungi (mold and mildew)	SPRAY: Apply to clean carpet surface. Using a trigger pump sprayer or pressure sprayer, spray the entire surface area 4"- 6" from the surface making sure the surface is completely covered. For rotary jet extraction cleaners and carpet steamers, add EnviroSystems® BioShield® 75 directly to the cleaning tank, then operate the equipment in accordance with manufacturer's instructions. Apply and then let stand until dry. Test staining and color-fastness of carpets by treating and drying a small concealed area prior to application. EnviroSystems® BioShield® 75 treats approximately 200 square feet per gallon (50 square feet per quart). When treating coarser substrates (e.g., wool carpeting), more EnviroSystems® BioShield® 75 may be required due to absorption. Dry carpet areas and surfaces before re-entry. A fan may be used to assist in drying carpeting. Remove children and pets from treated area until completely dried. If necessary, reapply EnviroSystems® BioShield® 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, and mildew stains return.
Mattress pad and mattress ticking and upholstery composed of acetates, acrylics, cotton, fiberglass, nylon, polyester, polyethylene, polyolefins, polypropylene, rayon, spandex, vinyl, wool; fiberfill to be used in upholstery, sleeping bags, apparel, where the fiber is cotton, natural down, nylon, rayon or wool	Odor causing bacteria, bacteria which cause staining and discoloration, and fungi (mold and mildew)	SPRAY: Clean surfaces prior to application. Using a trigger pump sprayer, spray the entire surface area 4"- 6" from the surface making sure the surface is completely covered. Apply and then let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test staining and color-fastness of fabric by treating and drying a small concealed area prior to application. When applying to mattress pads and ticking do not soak. Remove children and pets from treated area until completely dried. If necessary, reapply EnviroSystems® BioShield® 75 every three months or when odor, staining and discoloration due to bacteria, mold stains and mildew stains return.
Tents, tarpaulins, sails, ropes	Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew), and algae	SPRAY: Clean surface prior to application. Using a trigger pump sprayer or pressure sprayer, spray the entire surface area 4"-6" from the surface making sure the surface is completely covered. Let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. Test staining and color-fastness of fabric by treating and drying a small concealed area prior to application. If necessary, reapply EnviroSystems® BioShield® 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return. DIP/SOAK: Use appropriate sized wash basin or tub for dipping/soaking the item you are treating. Use enough EnviroSystems® BioShield® 75 to completely submerge item. Keep item in solution for three minutes. Remove item and wring excess liquid. Do not reuse solution after dipping/soaking. Dry treated articles before use. Substrates can be hang-dried at room temperature or at temperatures to a maximum of 160 °C (320 °F); (for example in a clothes dryer). Remove excess liquid before attempting to dry in a clothes dryer. If necessary, reapply EnviroSystems® BioShield® 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.
Roofing materials (such as shingles, roofing granules, wood shakes, felt, stone, synthetic overcoats)	Odor causing bacteria, bacteria which cause staining and discoloration, fungi (mold and mildew), and algae	SPRAY: Make sure the roof is clean prior to application. Using a pressure sprayer, spray the entire surface area 6"-12" from the surface making sure the surface is completely covered. After applying EnviroSystems® BioShield® 75, let stand until dry. EnviroSystems® BioShield® 75 treats approximately 200 square feet of roofing per gallon (50 square feet per quart). If necessary, reapply EnviroSystems® BioShield® 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, mildew stains, and algae stains return.

	Pest controlled	Method of Application
Buffer (polishing and abrasive), Polyurethane and cellulose foam for household mops, vacuum cleaner bags, umbrellas, casual shoes, athletic shoes	Odor causing bacteria, bacteria which cause staining and discoloration, and fungi (mold and mildew)	SPRAY: Clean surface prior to application. Using a trigger pump sprayer or pressure sprayer, spray the entire surface area 4"-6" from the surface making sure the surface is completely covered. Let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. If necessary, reapply EnviroSystems® BioShield® 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, and mildew stains return.
	Pest controlled	Method of Application
Tubs, glazed tiles, vanity tops, shower curtains, shower stalls (areas), sinks, washable walls, wall paper for non-food contact, floors, window sills, cabinets, garbage cans, appliances, refrigerators (exterior), fiberglass, formica, glazed tiles, glazed porcelain, synthetic marble, plastic, vinyl	Odor causing bacteria, bacteria which cause staining and discoloration, and fungi (mold and mildew)	SPRAY: Using a trigger pump sprayer, spray the entire surface area 4"- 6" from the surface making sure the surface is completely covered. Let stand until dry or let stand 3 minutes and wipe dry with cloth or sponge. If spotting occurs, wipe with moist cloth or sponge. If necessary, reapply EnviroSystems® BioShield® 75 every three months or when odor, staining and discoloration due to bacteria, mold stains, and mildew stains return.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage and disposal.

Pesticide Storage: Store in original, tightly closed containers below 30°C (86°F) and above 0°C (32°F) in a secure area inaccessible to children and away from food or feed.

Pesticide Disposal: Residential Use - Wastes resulting from the use of this product may be disposed of on site.

Commercial/Industrial Use - Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

Container Disposal: Residential Use - Securely wrap original container in several layers of newspaper and discard in trash.

Commercial/Industrial Use - Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

FOR MORE INFORMATION CONCERNING THIS PRODUCT, PLEASE CONSULT THE MATERIAL SAFETY DATA SHEET (MSDS). THE MSDS CAN BE OBTAINED BY CONTACTING INDUSCO, LTD. AT 2319 JOE BROWN DRIVE, GREENSBORO, NC, 27405, (336) 375-7555.

IMPORTANT: WARRANTY AND DISCLAIMER INFORMATION

IndusCo, Ltd., warrants that the product conforms to its chemical description and is reasonably fit for the purposes stated in this bulletin when used in accordance with directions under normal conditions of use; but this warranty of fitness for a particular purpose does not extend to the use of this product contrary to bulletin instructions, or under abnormal conditions, or under conditions not reasonably foreseeable to the seller, and buyer assumes the risk of any such use. INDUSCO, LTD. SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY, INCLUDING THE WARRANTY OF MERCHANTABILITY.

Sold by: **INDUSCO, LTD.**

2319 Joe Brown Drive, Greensboro, NC 27405

(336) 375-7555 FAX (336) 375-0826

ESL082008 REV091808