MATERIAL SAFETY DATA SHEET

			••	_					Designation of the
SECTION 1 - I	MAN	JUF	AC	TU	RER	OR	SUP	PLIER	DATA

			101000
MANUFACTURER'S NAME & MAILING ADDRESS	PREPARED BY	SIGNATURE	ν.
U S Chemical Corporation	D. E. Kenas	David C.	Kenas
316 Hart Street	TITLE	7.7	DATE
Watertown, Wisconsin 53094 USA	Quality Assurance 1	tanager	12-20-99
EMERGENCY TELEPHONE NO. (24 HOUR SERVICE)	PRODUCT INFORMATION TELL	EPHONE NO. (8 AM TO 5 PM	CST, MON - FRI)
Medical Emergency ONLY: 1-800-851-7145 Ext. 075	Product Information: 1-800-558-9566		

1	0	6	C
	1	10	186

SECTION 2 - IDENTITY OF MATERIAL

PRODUCT NAME		EMPERATUR	E LAUNDRY	DET	ERGENT /	
Alkaline L	APTION aundry Deter	gent			FORMULA Proprietary Blend	CHEMICAL FAMILY N.A.
PEGULATED	DOT PROPER SHIP Not Regulat	PING NAME •d by D.O.T.				
DENTFICATION	SHIPPING ID NUM N.A.	BER PACKING GROUP N.A.	HAZARO CLASS N.A.			

SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT	SPECIFIC GRAVITY (HaO = 1)	PHYSICAL FORM	COLOR
N.A.	N.A.	Granular Powder	White
VAPOR PRESSURE (mm Hg)	MELTING POINT	SOLUBILITY IN WATER	SCENT
N.A.	N.A.	Moderate	Floral
VAPOR DENSITY (AIR = 1)	EVAPORATION RATE (BUTYL ACCTATE - 1)	pH 2500 ppm SOLUTION	PH CONCENTRATE
N.A.	N.A.	11.2	N.A.
OTHER			
N.A.			

SECTION 4 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

[CHEMICAL NAME: COMMON NAME]	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	PERCENT WT/WT
Sodium Metasilicate	Not	Not	2 mg/m3	10.0
CAS Registry Number 6834-92-0	Established	Established	Ceiling Limit (PQ Corporation)
Sodium Carbonate: Soda Ash	Not	Not	Not	40.0-70.
CAS Registry Number 497-19-8	Established	Established	Established	
STATE RIGHT TO KNOW INFORMATION				
THIS PRODUCT CONTAINS: SODIUM CARBONA MONOXYNOL/9016-45-9	TE/497-19-8, SODIUM CH	ORIDE/7647-14-5	SODIUM METASILICA	TE/6834-92-0,
THIS PRODUCT CONTAINS: SODIUM CARBONA MONOXYNOL/9016-45-9				TE/6834-92-0,
THIS PRODUCT CONTAINS: SODIUM CARBONA MONOXYNOL/9016-45-9	Reactivity-0 See Sec	tion 5 for Prote	ective Equipment.	TE/6834-92-0,
THIS PRODUCT CONTAINS: SODIUM CARBONA MONOXYNOL/9016-45-9 MFPA RATING: Health-2/Flammability-0/	Reactivity-0 See Sec	tion 5 for Prote	octive Equipment.	TE/6834-92-0,
THIS PRODUCT CONTAINS: SODIUM CARBONA MONOXYNOL/9016-45-9 NFPA RATING: Health-2/Flammability-0/	Reactivity-0 See Sec	tion 5 for Prote	octive Equipment.	TE/6834-92-0,

This product does not contain any known carcinogens or anticipated carcinogens according to the criteria of the NTP Annual Report on Carcinogens, IARC Monographs, and OSHA 29 CFR 1910, Subpart Z.

(CONTINUED IN SECTIONS 5 TO 8)

V	DECTION O' ON E	DUNGE DATE.
PROTECTIVE	EYES Safety glasses with side shields and an eye-wast	h station.
EQUIPMENT TYPES	PESPEATORY Dust mask if handling creates air-borne dust.	QLOMS Rubber or Neoprene.
1	OHER If major exposure is possible to eye/skin, wear	/use appropriate protective equipment.
	GENERAL MECHANICAL Satisfactory, Maintain adequate ventilation.	Keep levels below recommended TLV.
ENTILATION	NOT ordinarily needed. Avoid inhalation of dus	t containing this product.
	HANDLING & STORAGE. Follow all label directions. precautions, and first-aid measures. Avoid inh	Instruct personnel about proper use, hazards, alation, ingestion and contact with skin and eyes.
PRECAUTIONS	Rotate stock regularly. Handle carefully to avnot in use. Recommended storage temperature be	oid damaging container. Keep container closed when low 100°F; Keep out of children's reach.

SECTION 6 - HEALTH HAZARD DATA

	NAMED AT NO MAN AND ADDRESS OF THE PROPERTY OF				
EFFECTS OF EXPOSURE	NASTION May dause nauses, vomiting, and tissue damage to mouth, esophagus, stomach, and to other				
	tissues with which contact is made. Severity depends upon degree of exposure.				
	SKING EYES SKIN: Contact may cause mild to severe irritation, depending on degree of exposure.				
	EYES: Corrosive, Causes eye burns. May cause temporary or permanent vision loss and blindness.				
	ACUTE & CHEONIC ACUTE: Irritation to skin and respiratory system. Causes eye burns. Permanent eye damage may result without immediate first aid treatment. CHRONIC: None Known.				
NTRY	NOGSTION-X SKIN ABSORPTION- TARGET ORGANS IKIN-X EYES-X INMALATION-X EYES.				

SECTION 7 - PHYSICAL HAZARD DATA

FLAMMABILITY	LEL = N.A.		FLASH POINT = N.A. METHOD USED = N.A.
	STABLE	x	CONDITIONS TO AVOID Avoid mixing with any other cleaning product. Mix only with wate Avoid temp. >100°F and high humidity as these conditions contribute to caking.
STABILITY	UNSTABLE		PAZAPOOUS DECOMPOSITON PRODUCTS Warning: Mixing with incompatible materials may produce carbon dioxide, hydrogen, and other toxic and irritating fumes.
HAZARDOUS	MAY DCCUR .		CONDITIONS TO AVOID
POLYMERIZATION	WILL NOT DOCUR	X	N.A.
INCOMPATIBILITY	Acidic mater		and oxidizing agents such as sodium hypochlorite or bleach.

	EXTINGUISHING MEDA. For fires in area, use appropriate media. For example: Water spray, dry chemical, carbon dioxide, or alcohol foam.
FIRE	SPECIAL PROCEDURES Evacuate area of unprotected and unnecessary personnel.
	UNUSUAL HAZAROS . Not Applicable.
FIRST AID MEASURES	INGESTION: Do not induce vomiting. If patient is conscious and can swallow, administer milk or water. SKIN: Ramove contaminated clothes, flood with water for 15 minutes. EYES: Flood with lukewarm (not hot) water poured from a large glass 2 or 1 inches from eyes. Ramove contacts. Have patient blink as much as possible while flooding the eyes. Continue for 15 minutes. INUALATION: Move victim to fresh mir. Give artificial respiration if patient is not breathing. ADMINISTRE FIRST AID TREATMENT AS STATED ABOVE, THEN CALL 1-800-851-7145 Ext 075 OR CONTACT PHYSICIAN FOR FURTHER MEDICAL INSTRUCTIONS.
BPILLS RG -	STEPS TO BE TAKEN Use proper protective equipment. Carefully sweep up and shovel into dry containers without raising dust. Cover containers and move containers out of spill area. Flush area with water and follow with normal clean-up procedures.
RQ - N.A.	WASTE DEPOSAL METHOD Comply with all federal, state, and local regulations. Consult state and local authorities for restrictions on disposal of chemical waste. Please recycle empty container whenever possible.

THE DATA IN THIS MATERIAL SAFETY DATA SHEET PELATES ONLY TO THE SPECIFIC MATERIAL DESCRIATED AND DOES NOT PELATE TO ITS USE IN COMBRIATION WITH ANY OTHER MATERIAL OR PROCESS. THE DATA CONTROL THE BELEVEN TO BE ACCURATE, SINCE US CONDITIONS VIATY AND ARE OUTSEC USE CONTROL. THE MANUFACTURER MATERIAL OR PROCESS. THE DATA CONTROL, THE MANUFACTURER MATERIAL OR PROCESS. THE DATA OF PRESENCE OR MATERIAL OR ASSUMES NO LUBLISTY OF PRACTICE TO DESCRIPTIONS OF THE OFFICE OFFICE OF THE OFFICE OF THE OFFICE OF THE OFFICE OFFIC

