

MATERIAL SAFETY DATA SHEET
(MSDS)

Disinfectant

ITEM NUMBER: 015 - HEALTH CARE USE DISINFECTANT

IDENTITY (As Used On Label and List): PROLINK HEALTH CARE DISINFECTANT

Emergency Medical Telephone Number 1-800-228-5635 (24 HRS)

PRODUCT HAZARD RATINGS: - Health = 1, Fire = 4, Reactivity = 0, Protective Equipment = *B (HMIG)
(Rating Legend: - 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal)

Section I

PREFERRED DISTRIBUTORS, INC.
16607 BLANCO ROAD
SAN ANTONIO

TELEPHONE NUMBER FOR INFORMATION:
1-210-493-1191

TX 78232

DATE PREPARED: 01/11/94
NAME OF PREPARER: Philip T. Miller

Section II - Hazardous Ingredients/Identity Information

Chemical Names	Exposure Limits (LD50-Oral Rat)	SARA Title-III SEC 313	ACGIH TLV/TWA	OSHA PEL	% By Wt.
Ortho Phenyl Phenol (CAS #90-43-7)	2000mg/kg	-	NE	NE	0.1-0.5
Para Tertiary Amylphenol (CAS #80-46-6)	1830mg/kg	-	NE	NE	0.0-0.1
SDA 3A Denatured Alcohol (mixture: water, Ethyl & Methyl Alcohol)					55-60
A. Methyl Alcohol (CAS #67-56-1)	5.6g/kg	Yes	200ppm	200ppm	-
B. Ethyl Alcohol (CAS #64-17-5)	13.7g/kg	-	1000	1000	-
Sodium Nitrite (CAS #7632-00-0)	85mg/kg	-	NE	NE	0.1-0.5
Ammonium Hydroxide (CAS #1336-21-6)	350mg/kg	-	25 (ammonia)	50	0.0-0.5
Liquified Petroleum Gas (CAS #68476-85-7)	NE	-	1000	1000	25-30

Unidentified ingredients are not considered hazardous under the Federal Hazard Communication Standard.
Components Listed As A Suspected Carcinogen: None

Section III - Physical Characteristics

Boiling Point: NA Vapor Pressure (psig): 125@130F Specific Gravity (H2O=1): <1.0
Solubility/Water: Appreciable Vapor Density (AIR=1): >1 Evaporation Rate (Ether=1): <1
Appearance and Odor: Wet misty spray, lemon odor.

Section IV - Fire and Explosion Hazard Data

Aerosol Flammability: This product is considered to be Flammable as described in 16CFR 1500.45.
Flammable Limits - % Volume In Air (Propellant): LEL: 1.8 UEL: 9.7
Extinguishing Media: Carbon dioxide, foam and/or dry chemical may be used.
Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up.
Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers.
Unusual Fire and Explosion Hazards: At elevated temperatures (over 54C-130F) containers may vent or burst.

Section V - Reactivity Data

Stability: Stable Hazardous Polymerization: NA
Incompatibility (Materials to Avoid): Strong oxidizers, heat and flame.
Hazardous Decomposition Products: Carbon monoxide, carbon dioxide and additional toxic chemicals may be formed in small amounts.
Conditions to Avoid: Do not store above 54C-130F. Keep away from heat, direct sunlight, open flames or sparks. Dropping of containers may cause bursting.